

bizhub press // 1250/1052

Production Printing System



Expanding the possibilities of monochrome digital PRESS.



Meet tight deadlines with greater productivity

High-speed printing for short runs and guick turnarounds

- 125 ppm (A4 horizontal), 70 ppm (A3)
- Significantly faster RIP speed with new CPU and optimised data processing

High paper capacity and on-the-fly consumable replacements

- Max. paper capacity: 15,000 sheets with the large capacity paper feeding units*. Auto-tray switch function keeps operations going without missing a beat.
- High-capacity toner can be replaced on the fly.
- Large-capacity stacker* with cart holds up to 15,000 sheets (with 3 stackers).

* Optional







Note: All paper capacities for 80 g/m² paper



Create more business with greater paper handling

Register up to 256 types of paper with the Paper List (profile)

Greater thin and thick paper support

40 g/m² thin to 350 g/m² thick paper stock* * Thick paper support available only for optional Paper Feed Unit PF-703 and Paper Feed Unit PF-706 middle trays.



Full A3 outputs including crop marks

■ Max. 324 × 483 mm paper (314 × 483 mm printable area)* * PF-703 required

Coated paper & embossed paper support

Envelope printing

- New envelope fuser unit option*
 - * Paper other than envelopes cannot be fed when using the envelope fuser unit.

Note: Please consult your service engineer for details regarding recommended paper, and envelope types and sizes



Error-free operation from start to finish

Air suction paper feeding system

The high capacity Paper Feeding Unit PF-703* adopts an air suction paper feeding system that better adheres the paper to the conveyance belt for stable conveyance at all times. * Optional

Multi-feed detection sensor


An ultrasonic sensor detects multi-feeding to prevent blank pages from being mixed in with the output.


Paper skew sensor

This sensor detects paper skews to prevent misaligned printing.

Hybrid decurling system*

The Relay unit RU-509* employs a mechanical decurler and a humidifier-type decurler HM-102* to prevent paper curls. Each system is used according to the paper type to maintain high quality outputs even for booklets.





input section

Humidifier type decurler (HM-102)


* Optional





From hole punching, folding, corner and centre stapling to perfect binding, high-performance, high-productivity inline finishers allow the bizhub PRESS 1250/1052 to be optimally expanded to handle an abundance of orders.

In-line finishing options






Impressive image quality like never before

LED Print Head for 1,200 dpi high resolution outputs


Achieve true 1,200dpi resolution outputs with the LED Print Head (LPH) which offers clearer reproduction of small text and smoother halftones.



Highly accurate duplex registrations

Highly accurate front-to-back-side registrations are possible with image shift and independent magnification adjustment. Even the slightest shifts can be minutely adjusted to achieve higher quality results for duplex printing, trimming and bookbinding.







- Relay Unit RU-509 Relay unit with mechanical decurler
- Relay Unit RU-510 Relay unit with 2-ply reversal Notes: Required for bizhub PRESS 1250. equired for bizhub PRESS 1052 when equipped with PI-PFU – large-capacity cover sheet feeder that equips FA-501 to PF-703.

Tone curve utility

Fine tune brightness and contrast before printing without a dedicated software. Tone curve utility corrects these without affecting the density of text for true professional results.





is 100% blac

Maintaining 100% density for text 100% density can be maintained for text without affecting the correction results of the tone curve.

High quality reproduction and low temperature fixing with Simitri HD toner

s

Simitri HD High Definition Polymerized Toner

Other functions -

- Halftone noise reduction
- Advanced technologies that control uneven densities caused by differences in document and developing conditions
- Ozone concentration reduction of band electrode
- Belt transfer system for improved transferred image quality and paper feeding



Improve workflow efficiency with job management

Streamline complex output operations with flexible workflow management.

- Job list display
- Job ticket editing
- Job schedule management



Highly rigid frame and highly durable parts

The bizhub PRESS 1250/1052 are built to withstand heavy and continuous use. The highly rigid frame with box-shaped dual-structured chassis prevents the main unit from vibrating and twisting for longer lasting performance.



Other functions -

LDAP support



Job ticket editing



Use of recycled materials

Environmentally considerate recycled PC/PET and plant-based bioplastic are employed throughout the bizhub PRESS 1250/1052.

Centralised management and TCO reduction

Numerous cost-saving technologies are employed throughout the bizhub PRESS 1250/1052. And centrally manage all output devices with PageScope Enterprise Suite for smoother operation.

峰 🕬 Enterprise Suite





For more information please visit the bizhub Web site at http://www.biz.konicaminolta.com/production/1250_1052/index.html



Product appearance, configuration and/or specifications are subject to change without notice. This product is not available for some countries or regions.

KONICA MINOLTA, the KONICA MINOLTA logo and symbol mark, "Giving Shape to Ideas", bizhub pRO, bizhub PRO, bizhub PRESS, magicolor, PagePro, PageScope, Simitri, Simitri HD, Simitri HD+, Simitri with Biomass, Emperon, S.E.A.D., S.E.A.D.II, Printgroove and Konica Minolta Optimised Print Services and their respective logos are registered trademarks or trademarks of KONICA MINOLTA, INC. All other brands and product names are registered trademarks or trademarks of their respective companies or organisations.



Ecology & Environment

KONICA MINOLTA products are designed with the environment in mind.

- Eco-friendly Toners Production at ISO Certified Factories
- RoHS Compliance WEEE Compliance
- ONICA MINOLTA

Energy Star

From consulting, system design, to operations, Konica Minolta offers total support to optimise your office output environment.

http://www.biz.konicaminolta.com/services/ops

🗥 Requirements for safe use

OPTIMISED

- Please read and follow the instruction manual to ensure safe operation
 Only operate using appropriate power supply and voltage.

· Connecting the earth wire to an inappropriate place may cause explosion or electric shock. Please connect accordingly (Taiwan and the Philippines only).

KONICA MINOLTA, INC.

2-7-2 Marunouchi Chiyoda-ku, Tokyo, Japan http://www.biz.konicaminolta.com



ISO15408 (EAL Level 3) Certification

These products comply with the security requirements of ISO15408 (EAL Level 3).

The ISO 15408 certification applies only to IT security capabilities. This certification is NOT a product guarantee